Sobolev scalar products in the construction of velocity models

Petr Bulant, **Luděk Klimeš** and **Karel Žáček**
Department of Geophysics, Charles University, Ke Karlovu 3, 121 16 Praha 2, Czech Republic.
E-mails: bulant@seis.karlov.mff.cuni.cz, klimes@seis.karlov.mff.cuni.cz,
zacek@karel.troja.mff.cuni.cz

Summary

The minimization of the Sobolev norm during linearized inversion of given data enables to control the model parameters unresolved by the data being fitted.

Even if a reasonably looking model can be obtained without minimizing the Sobolev norm, it may be too rough for some computational methods. We may construct models optimally smooth for given computational methods by minimizing the corresponding Sobolev norm during the inversion.

Probably the smoothest models are required by the ray methods. The efficiency of ray tracing can be evaluated in terms of the "average Lyapunov exponent" for the model. The "average Lyapunov exponent" may be approximated by the square root of the corresponding Sobolev norm of the model, which allows models optimum for ray tracing to be constructed.

1 Sobolev scalar products and Sobolev norms

We define the Sobolev scalar product (see, e.g., Tarantola 1987) of real–valued functions f and g as a linear combination of the L_2 Lebesgue scalar products of the zero, first, second or higher derivatives of the functions:

$$((f,g)) = \left[\int \mathrm{d}\mathbf{x}\right]^{-1} \sum_{ij\ldots} \sum_{ab\ldots} \int \mathrm{d}\mathbf{x}\, b_{ij\ldots|ab\ldots}\, f_{,ij\ldots}(x_p)\, g_{,ab\ldots}(x_q) \quad , \tag{1}$$

where $\int \mathrm{d}\mathbf{x}$ is the definite integral over the model volume, and $b_{ij\ldots|ab\ldots}$ are real-valued coefficients of the linear combination. The linear combination should preserve the properties required of scalar products (symmetry and positiveness). The maximum number of indices $ij\ldots$ and $ab\ldots$ in (1) equals the maximum order of the considered derivatives, the indices take the values from 1 to 3 in 3-D, 1 to 2 in 2-D and 1 in 1-D.

The Sobolev norm of a velocity model may, in general, be composed of the zero, first, second or higher derivatives of the functions describing the model. The model is very often described by cubic, bicubic or tricubic splines. Since the third homogeneous partial derivatives of the splines are discontinuous, the Sobolev scalar product composed of the fourth and higher derivatives could be infinite, and thus should be avoided. Simultaneously, minimization of the (zero derivatives of the) model functions usually has no meaning. We thus usually consider only Sobolev norms composed of the first, second and third derivatives. Since studies of the third derivatives have not yet been finished, we will concentrate on the first and second derivatives.

2 Including the Sobolev norm in the objective function for inversion of seismic data

The minimization of the Sobolev norm during linearized inversion of given data enables to control the model parameters unresolved by the data being fitted. For example, if we are fitting discrete values of a material parameter with a smooth function, the properties of interpolation between the discrete values may be controlled by means of minimizing the square of the selected Sobolev norm of the function.

Even if a reasonably looking model can be obtained without minimizing the Sobolev norm, it may be too rough for some computational methods. The errors of many computational methods may be approximated by a function dependent on the Sobolev norm of functions describing the model. We may thus construct models optimally smooth for given computational methods.

In the case of ray methods, the situation is more complicated. The feasibility and efficiency of ray tracing imposes relatively strong requirements on the smoothness of the velocity models, but, unfortunately, we still have no quantitative criteria of applicability and accuracy of ray methods or their extensions. On the other hand, the numerical efficiency of ray tracing can be evaluated in terms of the "average Lyapunov exponent", introduced by Klimeš (1999, 2000b) for 2-D models without structural interfaces.

2.1 Fitting discrete values and regularizing an ill–conditioned inversion

Assume that we are fitting discrete values u^α at points $\mathbf{x}^\alpha$ inside the model volume by minimizing objective function

$$y = \sum_\alpha [\tilde{u}(\mathbf{x}^\alpha) - u^\alpha]^2 [\Delta u^\alpha]^{-2} + S^2 (\!(\tilde{u}, \tilde{u})\!) \quad , \tag{2}$$

where Δu^α is a given deviation of model $\tilde{u}(\mathbf{x})$ from values u^α at points $\mathbf{x} = \mathbf{x}^\alpha$. For infinitely small weighting factor $S \to 1$, the limit form $\tilde{\tilde{u}}(\mathbf{x}) = \lim_{S \to 0} \tilde{u}(\mathbf{x})$ of the solution corresponds to the minimization of objective function $y = (\!(\tilde{\tilde{u}}, \tilde{\tilde{u}})\!)$ with boundary conditions $\tilde{\tilde{u}}(\mathbf{x}^\alpha) = u^\alpha$.

The properties of interpolation between discrete values by means of minimizing the squares of different Sobolev norms has been investigated by Klimeš (2000a). He showed that the Sobolev norm composed of second derivatives of model functions is suitable for fitting discrete values.

Assume that we are fitting a structural interface with a smooth function. In such a case the data for the function are available only in that part of the model, where the interface is located. The behaviour of the function in other parts of the model is not given by the data, see Figure 3. We might control the function by adding new artificial points to the data for the interface, but this manual intervention would probably slightly distort the modelled interface. It is much more convenient to control the function by increasing the weighting factor S of the Sobolev norm. A small increment of S will not influence the function in the region with the data, but will regularize its behaviour in the remaining parts of the model.

2.2 Constructing seismic models of optimal smoothness for a selected numerical method

The Sobolev norm is usually included in the inversion of seismic data if the numerical method to be applied to the model requires a smooth model. The Sobolev norm included in the objective function acts as a low–pass wavenumber filter (Klimeš 2000a).

We assume the objective function for the inversion of slowness or velocity $u(\mathbf{x})$ in the form of

$$y = \left[\int \mathrm{d}\mathbf{x} \right]^{-1} \int \mathrm{d}\mathbf{x}\, \tilde{C}(\mathbf{x}, \mathbf{x}) + S^2 \|u\|^2 \quad , \tag{3}$$

where $\tilde{C}(\mathbf{x}, \mathbf{x})$ is the covariance function describing the deviation of model $\tilde{u}(\mathbf{x})$ from geological structure $u(\mathbf{x})$ (Klimeš 1997), and S is the weighting factor of the Sobolev norm $\|u\|$ of the functions describing the model.

The first summand in (3) is the mean squared difference between the model and the geological structure. It is then advantageous if $S\|u\|$ approximates the r.m.s. difference of the results of the numerical method under consideration from the exact solution in the model, expressed in the units of $u(\mathbf{x})$. Objective function (3) then gains the clear physical meaning of the squared deviation

between the model and the geological structure plus the squared deviation between the exact and the numerical results in the model, expressed in the units of $u(\mathbf{x})$.

The selection of the Sobolev scalar products for particular numerical methods has been demonstrated by Klimeš (2000a) on examples of centred finite differences of the second order, network shortest–path ray tracing, 2-D first–order grid travel time tracing, and 2-D second–order grid travel time tracing.

2.3 Constructing seismic models for ray tracing and Kirchhoff migrations

In complex models, the behaviour of rays becomes chaotic and the geometrical spreading, number of arrivals and density of caustic surfaces increase exponentially with travel time. The exponential increment may be quantitatively described in terms of the "average Lyapunov exponent" for the model. The "average Lyapunov exponent" may roughly be approximated by the square root of the Sobolev norm composed of the second partial derivatives of the functions describing the slowness or velocity field in the model (Klimeš 2000a). This enables us to determine the quantitative criteria on models, so as to be suitable for ray tracing, in terms of Sobolev scalar products. We choose the maximum "average Lyapunov exponent" for the model, we estimate the maximum Sobolev norm of the model, and we estimate the value of weighting factor S. We then perform the inversion, compute the values of the "average Lyapunov exponent" and the Sobolev norm in the inverted model, re-estimate the value of S, and continue iteratively with the inversion until we obtain the model of the required smoothness.

3 Numerical example – smoothing 2-D model Hess for Kirchhoff migrations

Routines for application of the above described minimization of the Sobolev norm during the seismic inversion have been coded in Fortran 77. The software used for the computations is available at http://seis.karlov.mff.cuni.cz/consort/software. All the computations are carried out on a PC Pentium with 64 Mbytes of memory.

The 2-D model Hess has horizontal dimension 40200 feet and vertical dimension 21000 feet. Two interfaces in the model, limiting a salt body, are discretized on a grid of 64 points spaced at 200 feet. Background velocities are discretized on a grid of 202×106 points with a spacing of $200\,\mathrm{ft} \times 200\,\mathrm{ft}$; the velocity inside the salt body is constant. Originally, each data point is considered to be a model spline point, and the number of model parameters is thus $64 + 64 + 1 + 202 \times 106 = 21541$. See Figure 1.

We perform several tests of ray tracing in the original model. The behaviour of the ray field seems to be too complicated with too many caustics, especially in the low velocity channel near the surface of the model, see Figure 2. We thus decide to smooth the model by means of inversion of the given data with minimization of the Sobolev norms of the velocity field in the model.

We choose a new parameterization of the model as follows: for the interfaces we take an irregular B–spline grid of 28 points with 26 points regularly spaced at 500 feet in the region of the salt body and 2 points at the sides of the model. The two points enable us to control the behaviour of the functions describing the interfaces in the parts of model not covered by the data for the interfaces, see Figure 3. For the background velocity, we take a horizontally regular grid of 26 points spaced at 1600 feet and a vertically irregular grid of 58 points spaced at 200 feet at the top to 400 feet at the bottom. The number of model parameters is thus $56 + 1 + 26 \times 58 = 1565$.

The standard relative velocity deviation of the velocity in the inverted model from the velocity in the original model is 0.18 %. The standard deviation of the interfaces is 5.6 ft, which causes a travel time error of approximately $3.15\ 10^{-4}$ s. Figure 4 shows, how the smoothing of the velocity field by including the Sobolev norm in the velocity inversion regularizes the chaotic behaviour of rays.

Conclusions

The minimization of the Sobolev norm of the model during linearized inversion of given data enables us to control the model parameters unresolved by the data being fitted. For many computational methods it enables us to minimize not only the difference between the data and the model, but also the difference between the results obtained by the method to be used and the exact solution.



Figure 1: P-wave velocity in the original model. Horizontal dimension of the model is 40200 feet, its vertical dimension is 21000 feet. The background velocity varies from 5000 $\mathrm{ft\,s^{-1}}$ at the top of the model to 9800 $\mathrm{ft\,s^{-1}}$ at the bottom. The velocity of the salt body is constant and equals 14800 $\mathrm{ft\,s^{-1}}$.



Figure 2: The numbers of travel times and the rays computed for the refracted wave in the original model. The point source is located in the top left corner of the model. The white colour corresponds to no travel time, the individual shades of grey correspond to numbers of arrivals. The maximum number of arrivals is 11.



Figure 3: Inversion of the interfaces without the Sobolev norm. The oscillations of the surfaces limiting the lenticular salt body produced another spurious salt body on the right–hand side of the model.



Figure 4: The numbers of travel times and the rays computed for the refracted wave in the smoothed model. The source is again located in the left top corner of the model, the grey scale is the same as in Fig. 2. The maximum number of arrivals is 5.

The smoothness of the velocity field of the models constructed for the ray methods may be quantitatively described in terms of the "average Lyapunov exponent" for the model. The "average Lyapunov exponent" may be approximated by the square root of the corresponding Sobolev norm of the model. This enables us to construct the optimum models of geological structures for ray tracing, either by smoothing given rough models, or by inversion of seismic data.

Acknowledgements

This research has been supported by the Grant Agency of the Czech Republic under Contract 205/01/0927, by the Ministry of Education of the Czech Republic within Research Project J13/98 113200004, and by the members of the consortium "Seismic Waves in Complex 3-D Structures" (see http:/seis.karlov.mff.cuni.cz/consort/main.htm).

References

Klimeš, L. (1997): Accuracy and resolution of the travel–time tomography. In: Seismic Waves in Complex 3-D Structures, Report 6, pp. 13–24, Dep. Geophys., Charles Univ., Prague, available at http://seis.karlov.mff.cuni.cz/papers/r6lk1.htm .

Klimeš, L.: (1999): Lyapunov exponents for 2-D ray tracing without interfaces. In: Seismic Waves in Complex 3-D Structures, Report 8, pp. 83–96, Dep. Geophys., Charles Univ., Prague, available at http://seis.karlov.mff.cuni.cz/papers/r8lk1.htm .

Klimeš, L.: (2000a): Sobolev scalar products in the construction of velocity models. In: Seismic Waves in Complex 3-D Structures, Report 10, pp. 15–40, Dep. Geophys., Charles Univ., Prague, available at http://seis.karlov.mff.cuni.cz/papers/r10lk1.htm .

Klimeš, L. (2000b): Lyapunov exponents for 2-D ray tracing without interfaces. Expanded Abstracts of 70th Annual Meeting (Calgary), pp. 2293–2296, Soc. Explor. Geophysicists, Tulsa.

Tarantola, A. (1987): Inverse Problem Theory. Elsevier, Amsterdam.